

STAHLBAU-BREVIER

STEEL CONSTRUCTION BREVIARY





Table of contents – General overview

- 0 General blanks; (chapter 0.1.1 – 0.1.6, page 0/1 – 0/10)
- 0 Static formulas with examples of calculation; (chapter 0.2.1 – 0.14.2, page 0/11 – 0/66)
- 1 Bolted connections, grade 4.6, 8.8, 10.9,(HV), M12-M36; (chapter 1.1 – 1.6, page 1/1 – 1/22)
- 2 Tables of profiles: geometrical and static data
units-weights, diameter of bolts and holes, length in flange
datas of roof-inclination, drainages of roofs, selection of material,
function of circulation (division into 360° districts), increasement of beams
parabolics construction, coats of paintarea, round openings in webs of
HEA-, HEB- and IPE-profiles, essential tin-plate-thickness for bunkerwalls
in consequence of soilpressure, ceiling made of timber, matchwoodplates
supported on beams (timber), design of covers of platforms, wind- and
snowloading acc. to DIN 1055 part 5; (chapter 2.1 – 2.15, page 2/1 – 2/35)
- 3 Joints (front) shearing forced, single loaded M12 – M24, admissible shearing
Forces for IPE-, HEA- and HEB-profiles; (chapter 3.1.1 – 3.3.36, page 3/1 – 3/57)
- 4 Angles-joints (double) shearing forced, double loaded M12 – M24
secondary beam with notches at support; (chapter 4.1.1 – 4.6.2, page 4/1 – 4/31)
- 5 Angles-joints (double) shearing forced double loaded M12 – M24
secondary beam without notches at support; (chapter 5.1.1 – 5.2.7, page 5/1 – 5/15)
- 6 Stiffener joints (web) shearing forced, single loaded M12 – M24, S235 (St 37); (chapter
6.1 – 6.8.2, page 6/1 – 6/12)
- 7 Stiffener S235 (St 37) for HEA-, HEM- and IPE-profiles, admissible load F_z (kN) at
downside girder (flange) of bending beam, without stiffeners, bolted and fasten; (chapter
7.1 – 7.9.3, page 7/1 – 7/16)
- 8 Welded connections, stresses, tension, compression, shearing force, bending moment,
load capacity, technical details, examples of welding connections, support-plates; (chapter
8.1 – 8.7.1, page 8/1 – 8/15)
- 9 Supporting pillars (pinned connection), anchorage of pillar (anchorage like a walking
stick, dowels, bolts; (chapter 9.1.1 – 9.7.7, page 9/1 – 9/24)
- 10 Supporting pillars (rigid connection) fixed in quiver, crossbeam for erection U-iron 120,
160 and 200, fixlengths E, thickness of the shoe and connection (binding) to HEA-, HEB-
and IPE-profiles; (chapter 10.1.1 – 10.3.6, page 10/1 – 10/13)
- 11 Notches for HEA-, HEB- and IPE-profiles, geometry and transverse strength $F_{A,R,d} = V_{s,d}$; (chapter 11.1 – 11.20, page 11/1 – 11/24)
- 12 Workshop cranes, brackets, buffer, crane girder, crane rails, rails of strip steel, sections,
safety-distances; (chapter 12.1.1 – 12.7.8, page 12/1 – 12/35)
- 13 Rigid connections (HV-joints for HEA-, HEB- and IPE-profiles, calculation; (chapter 13.1.1
– 13.11.2, page 13/1 – 13/52)
- 14 Frame-corner, ridge joints bolted and welded; (chapter 14.1.1 – 14.11.2, page 14/1 –
14/22; chapter 14.12.1 – 14.12.2, page 14/23 – 14/24)
- 15 Support for beams without stiffeners HEB-, HEA- and IPE-profile; (chapter 15.1 – 15.3.3,
page 15/1 – 15/7)
- 16 Order of material, loading, roadcondition, transportation by lorry to site; (chapter 16.1 –
16.13.2, page 16/1 – 16/14)



Additional remarks to the contents of bar

Chapter 0: Blanks, static formula etc. examples of calculation

0/1-0/66

- BAR page 0/1-0/10: General blanks
- BAR page 0/11-0/22: Beam calculation of gantry cranes
- BAR page 0/23-0/26: Calculation of buckling length sky of single storeys according to DIN 4114
- BAR page 0/27-0/36: Overall stability, Buckling k_d , buckling due to bending B_{kd} , lateral torsional buckling B_{dKd} according to DIN 18800
- BAR page 0/37: Research thickness of solid ceiling made in ferro concrete
- BAR page 0/38-0/40: Cubic equation of bending moment according to Claperon
- BAR page 0/41-0/50: Static of civil engineering, loads for bending moments and moments of rigid moments, simply supported beam with cantilever beam at one and on both sides fixed, deflection of a simply supported beam
- BAR page 051-0/63: Calculation of construction parts and stress detection according to theory of deformation
- BAR page 0/64-0/66: Calculation of deflection for single and multiple beams e.g. beam of crane girder


Chapter 1: Bolted connections

1/1-1/22

- BAR page 1/1-1/2: Resistance and positioning of holes for bolts of grade 4.6 8.8 10.9=HV for $\alpha_L=3$ and $\alpha_L=2$
- BAR page 1/3-1/8: Designation of distances between bolts, sizes, press length
- BAR page 1/9-1/17: Determination of press length for short bolts, weight of bolts, female screw, washer, SI-screws
- BAR page 1/18-1/20: Bolts of grade 4.6 8.8 10.9=HV, ultimate limit force of shear- and bearing stress and positioning of holes for $\alpha_L=3$ and $\alpha_L=2$
- BAR page 1/21-1/22: Ultimate limit force of tensile and initial stress HV- and mechanical bolts grade 8.8 (DIN 931). Load capacity of shear force in thread is bigger (1.5) in a mechanical bolt as in a bolt (grade 4.6) used for steel construction. Due to press length can be graduated every 10mm the assortment of bolts can be reduced of the half. The length of thread of mechanical bolts is longer than for a normal. On that account less mechanical bolts for normal connections are necessary. In consequence of low load capacity of bearing stress for $\alpha_L=2$ smaller distances between bolts and border are necessary as for $\alpha_L=3$.

STAHLBAU-BREVIER

STEEL CONSTRUCTION BREVIARY



Chapter 2: Miscellaneous

2/1 – 2/34

- BAR page 2/1 – 2/5: Tables of profiles and selection of materials
- BAR page 2/6 – 2/10: Function of circulation, increasement of solid and framework beams (parabolic)
- BAR page 2/1 – 2/5: Tables of profiles and selection of materials
- BAR page 2/6 – 2/10: Function of circulation, increasement of solid and framework beams (parabolic)
- BAR page 2/11 – 2/13: Coat of paintarea for profiles
- BAR page 2/14 – 2/16: Details of round openings in webs of pillars (support) and ceilingbeam for the rolledsteel joist (I-profiles)
- BAR page 2/17 – 2/22: Proof of tin-plate-thickness for bunkerwalls, table of resistance for matchwoodplates, calculation of beams (timber), of solid ceiling, of cover for platforms (corrugated iron etc.)
- BAR page 2/33 – 2/29: Snow load DIN 1055 part 5 and addendum of July 2005
- BAR page 2/30 – 2/34: Wind load DIN 1055 part 4 August 1986, different kinds of concreteplates, specific weights, different kinds of supports
- BAR page 2/35: greek letters

Chapter 3: Joints (front), shearing forced, bolts M12, M16, M20, M24

3/1 – 3/57

- BAR page 3/1 – 3/5: Rules for shearing forces
- BAR page 3/6 – 3/45: Joints (Front), definitions and classification, ultimate limit force for shearing and bearing according to a thickness of 10 mm
 $F_{ARdL} = F_{ARdLEI} \times S_{vorh}$ (kN)
Bolts M12, M16, M20, M24 grade 4.6, 8.8
Bolts HVM20, HVM24 grade 10.9 length in flange
- BAR page 3/46 – 3/57: classification of bolts and joints


Chapter 4: Angles-joints (double), shearing force, beams with straight halved joint Bolts M12, M16, M20, M24 grade 4.6 and 8.8

4/1 – 4/31

- BAR page 4/1 – 4/9: Examples
- BAR page 4/10 – 4/17: Angles-joints (double), definitions and classification, ultimate limit force F_{ARd} for shearing and bearing according to a thickness of 10 mm,
 $F_{ARdL} = F_{ARdLEI} \times S_{vorh}$ (kN)
- BAR page 4/18 – 4/21: Classification of bolts and types of angles
- BAR page 4/22 – 4/25: For easy erection variation of angles-joints (double)
- BAR page 4/26 – 4/31: Positioning of holes e_1 , control-formular for load-limit of bolt

STAHLBAU-BREVIER

STEEL CONSTRUCTION BREVIARY



Chapter 5: Angles-joints (double), shearing force, beams without straight halved joint, Junction to IPE-beam, bolts M12, M16, M20, M24 grade 4.6 and 8.8

5/1 – 5/15

- BAR page 5/1 – 5/8: Angles-joints (double), definitions and classification, ultimate limit force F_{ARd} for shearing and bearing according to a thickness of 10 mm,
 $F_{ARdL} = F_{ARdLEI} \times S_{vorh}$ (kN)
- BAR page 5/9 – 5/15: Classification of bolts and types of angles

Chapter 6: stiffener joints (vertical web), shearing force, bolts M12, M16, M20, M24 grade 4.6 and 8.8

6/1 – 6/13

- BAR page 6/1 – 6/13: Web-plates, definitions and classification, ultimate limit force F_{ARd} for shearing and bearing according to a thickness of 10 mm, $F_{ARdL} = F_{ARdLEI} \times S_{vorh}$ (kN) for simple erection

Chapter 7: Stiffeners S235 (St 37)

7/1 – 7/16

- BAR page: 7/1 – 7/5,1: Stiffeners (full and semifull) connected to profiles HEA, HEB, HEM, IPE; geometry and designation of stiffeners incl. thickness and welded connections
- BAR page 7/6 – 7/16: Admissible load F_z (kN) at downside girder (flange) of bending beam, without stiffeners


Chapter 8: Welded connections

8/1 – 8/14

- BAR page 8/1 – 8/8: Notation, rules of load capacity and other details according to DIN 18800 part 7
- BAR page 8/9 – 8/14: Workmanship, geometry and dimensions, material and weld thickness and rough estimate for welding time

STAHLBAU-BREVIER

STEEL CONSTRUCTION BREVIARY



Chapter 9: Pillar (pinned connection)

9/1 – 9/

- BAR page 9/1 – 9/8: Anchorage of pillar with round bars dia. 20 and 24 mm in channels (anchorage like a walking-stick)
- BAR page 9/9-: Anchorage with dowel made by HILTI (M10, M12, M16, M20, M24) split- anchor (HTS) and combined-anchor (HVZ)
- BAR page 9/ - : Anchorage with plates and suspension tackle bolt dia. 22 x 150

Chapter 10: Supporting pillars (rigid connection), HEA-, HEB- and IPE-Profiles

10/1 – 10/13

- BAR page 10/1 – 10/3: Erection assistance of fixed pillars
- BAR page 10/4 – 10/7: Fixlength E_{erf} for pillar-profile HEA 200 – 1000, HEB 200 – 1000 and IPE 200 – 600
- BAR page 10/8 – 10/13: Thickness of the shoe d_p , binding with pressure (centre)

Chapter 11: Notches for HEA-, HEB- and IPE-Profiles, unilateral and bilateral


11/1 – 11/24

- BAR page 11/1 – 11/8: geometrical and static statements
- BAR page 11/9 – 11/16: Notches (uni- and bilateral) made by automatic cutting, geometry an ultimate limit forces
- BAR page 11/17 – 11/24: Notches (uni- and bilateral) made by manual cutting, geometry an ultimate limit forces

Chapter 12: Workshop cranes

12/1 – 12/35

- BAR page 12/1 – 12/7: Brackets: Geometry and ultimate limit forces $F_{PK,Rd}$, HEA/HEB 200 – 1000, IPE 240 – 600
- BAR page 12/8 – 12/13: Buffer (HEB 160-280), crane rail joints
- BAR page 12/14: Crane rails made from flat bars S 355 (St 52)
- BAR page 12/15 – 12/20: Crane girder and sections
- BAR page 12/21 – 12/35: Crane and crane rails: Technical datas, safety-distance, lifting classification and group of requirement, admissible deflections and tolerance of erection, overall stability and durability, pinned connection for crane girder



Chapter 13: Rigid connection (HV) for beams and frames (corner of frame)

13/1 – 13/52

- BAR page 13/1 – 13/13: Technical details and examples
- BAR page 13/14 – 13/23: Rigid girder connection HEA/HEB 120 – 1000, IPE 200 – 600,
- BAR page 13/24 – 13/49: Rigid frame-corners, HEA/HEB 120 – 1000, IPE 200 – 600,
- geometry, ultimate limit force, welds, additional stiffenerplates in framecorner
- BAR page 13/5 – 13/52: Dimension, covering plate for frame-corner, design of welds

Chapter 14: Construction of frame-corners

14/1 – 14/24

- BAR page 14/1 – 14/24: Examples, variants, performance (welded and bolted), conclusions, overall stability, single frame

Chapter 15: Distribution of force, endsupport of beams and crossing of beams

15/1 – 15/7

- BAR page 15/1 – 15/4: Computation, determination of coefficients
- BAR page 15/5 – 15/7: Geometry and ultimate limit forces $F_{EA,Rd}$, endsupport $F_{K,Rd}$, crossing of beams

Chapter 16: Supply of material, loading, transportation by lorry to site and roadcondition

16/1 – 16/14

- BAR page 16/1 – 16/14